



PROSLIDER CURVE

NATURAL BRASS
CURVABLE



EXAMPLES OF LAYING




PROSLIDER CURVE is a range of transition profiles that may be curved/shaped, with a special system of perforations allowing it to be bent so that particular geometric shapes may be easily obtained in situ. This allows decorative patterns to be created at will according to technical and aesthetic requirements. Recommended for joining floating floors in wood, melamine laminated wood and ceramics. It is made in natural brass in various heights, length 2.7 lm.



NATURAL BRASS thermo packed
bar length 2,7 LM - packaging 20 Pcs - 54 LM

Article	H mm		
PDONCV 08	8		
PDONCV 10	10		

COLOURS



ON - Natural Brass


(for a precise assessment of colours and finishes, see the relative enclosed sheet)

LAYING INSTRUCTIONS

1: Choose the PROSLIDER CURVE in the required height and material.
2: Cut the profile to the necessary length, calculating the total length.
3: Bend the profile mechanically with the PROCURVE MACHINE. 4: If necessary fix with screws and screw anchors, if used for floating floors in melamine/laminated wood, or simply insert the punched base under the floor laid with the same adhesive.

PROSLIDER CURVE

SILVER ANODISED ALUMINIUM
CURVABLE



SILVER ANODISED ALUMINIUM thermo packed
bar length 2,7 LM - packaging 40 Pcs - 108 LM

Article	H mm		
PDAACV 08	8		
PDAACV 10	10		

COLOURS



AA - Silver anod. alu.

(for a precise assessment of colours and finishes, see the relative enclosed sheet)

PROCURVE MACHINE

PROCURVE MACHINE - complete with wheels for all profiles

Page	Items / series available for	Minimum inside radius	Minimum outside radius
138	PTACCV	30 cm	30 cm
139	PTONCV	30 cm	30 cm
139	PTANCV	30 cm	30 cm
140	PELONCV	200 cm	300 cm
140	PELAACV	200 cm	300 cm
141	PRFONCV	200 cm	
141	PRFAACV	200 cm	
142	PJONCV	200 cm	300 cm
142	PJAACV	200 cm	300 cm
143	PINTAACV	300 cm	
143	PCRAA 149	80 cm	80 cm
143	PCR... 149	100 cm	100 cm
144	PDONCV	200 cm	
144	PDAACV	300 cm	

