


PROEND INS

GOLD, SILVER and BRONZE ANOD. ALUMINIUM
ADHESIVE and PUNCHED

stair nosing for existing steps

PED... 4528A
PED... 4528F
PED... 452816FS



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



Adhesive version

1: Choose the suitable profile and cut it to the necessary length.
2: Degrease, wash and clean the solid surface thoroughly. 3: Remove the protective paper from the adhesive. 4: Lay the profile by applying pressure evenly over the whole surface without using a hammer.

Punched version

1: Choose the suitable profile and cut it to the necessary length.
2: Mark the position of the holes using the existing holes in the profile as reference. 3: Insert the screw anchors into the drilled holes. 4: Fix the profile using flathead screws suitable for the relative slots in the profile.

PROEND INS is a step nosing profile in anodised aluminium with interchangeable rubber insert: the upper part is knurled to increase slip and slide resistance and is applied after laying. Available anodised with gold, bronze or silver finish and with adhesive or punched. **PROEND INS** ensures a perfect finish, covering laying defects and protecting the edge. Easy to lay with the self-adhesive backing ensuring perfect adherence to the step or with screws and screw anchors in the punched version.



ANODISED ALU. with adhesive WITH INSERT - thermo packed
bar length 3,30 LM - pack. 20 Pcs - 66 LM


| Article | H x L mm | | |
|--------------|----------|--|--|
| PED... 4528A | 28 x 45 | | |



ANODISED ALUMINIUM punched WITH INSERT - thermo packed
bar length 3,30 LM - pack. 20 Pcs - 66 LM

| Article | H x L mm | | |
|--------------|----------|--|--|
| PED... 4528F | 28 x 45 | | |

COLOURS



AA - Anod. silver aluminium AO - Anod. gold aluminium AB - Anod. bronze alu.
(for a precise assessment of colours and finishes, see the relative enclosed sheet)

ANOD. ALU. punched WITH INSERT, screws and screw anchors - thermo packed
bar length 1,65 LM - pack. 20 Pcs

| Article | H x L mm | | |
|-----------------|----------|--|--|
| PED... 452816FS | 28 x 45 | | |


Available in the finish: AA - AO - AB. The code of the selected colour must be added to the article code.
E.g.: PED... 4528A (chosen finish Anod. Gold) PEDAO 4528A.

BLACK INTERCHANGEABLE INSERT RUBBER

RUBBER

bar length 3,30 LM - pack. 20 Pcs - 66 LM


| Article | | | |
|---------|--|--|--|
| IIN 12 | | | |




PROEND

GOLD, SILVER and BRONZE ANOD. ALUMINIUM
ADHESIVE, WITHOUT HOLES and PUNCHED

stair nosing for existing steps



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



Adhesive version

1: Choose the suitable profile and cut it to the necessary length.
2: Degrease, wash and clean the solid surface thoroughly. 3: Remove the protective paper from the adhesive. 4: Lay the profile by applying pressure evenly over the whole surface without using a hammer.

Punched version

1: Choose the suitable profile and cut it to the necessary length.
2: Mark the position of the holes using the existing holes in the profile as reference. 3: Insert the screw anchors into the drilled holes. 4: Fix the profile using flathead screws suitable for the relative slots in the profile.


PROEND is a step nosing profile in anodised aluminium with silver-gold-bronze finish, available with self-adhesive backing or punched. Ideal for protecting existing steps and with knurled flat surface, it guarantees excellent safety features to prevent accidents in public and private environments.

PROEND ensures a perfect finish, covering laying defects and protecting the edge. Easy to lay with the self-adhesive backing ensuring perfect adherence to the step or using screws and screw anchors in the punched version.



ANOD. ALUMINIUM with and without adhesive - thermo packed
bar length 3,30 LM - pack. 20 Pcs - 66 LM

| Article | H x L mm | | |
|------------------------------|----------|--|--|
| PED... 48A (with adhesive) | 48 x 48 | | |
| PED... 48 (without adhesive) | 48 x 48 | | |



ANODISED ALUMINIUM punched - thermo packed
bar length 3,30 LM - pack. 20 Pcs - 66 LM

| Article | H x L mm | | |
|------------|----------|--|--|
| PED... 48F | 48 x 48 | | |

ANOD. ALU. punched with screws and screw anchors - thermo packed
bar length 1,65 LM - pack. 20 Pcs

| Article | H x L mm | | |
|---------------|----------|--|--|
| PED... 4816FS | 48 x 48 | | |

Available in the finish: AA - AO - AB. The code of the selected colour must be added to the article code.
E.g.: PED... 48A (chosen finish Anod. Gold) PEDAO 48A.



PROEND GRIP is a non-slip step nosing profile in anodised aluminium with adhesive non-slip 20mm thick insert in black carborundum to be fitted in the relative groove in the top of the profile upon completion of laying. The profile may be laid with fixing screws hidden afterwards by the adhesive carborundum, or with silicone and/or adhesive to be applied on the bottom of the profile, which is designed to ensure an excellent grip. It is made in anodised aluminium with silver, gold or bronze finish with anodising coat of approx. 15/20 micron.



SILVER, GOLD and BRONZE ANODISED ALU. with adhesive
bar length 3,4 LM - pack. 20 Pcs - 68 LM

| Article | H x L mm | | |
|---------------|----------|--|--|
| PEGR... 5230A | 52 x 30 | | |



SILVER, GOLD and BRONZE ANODISED ALUMINIUM punched
bar length 3,4 LM - pack. 20 Pcs - 68 LM

| Article | H x L mm | | |
|---------------|----------|--|--|
| PEGR... 5230F | 52 x 30 | | |

SILVER, GOLD and BRONZE ANODISED ALU. with adhesive
bar length 1,66 LM - pack. 20 Pcs

| Article | H x L mm | | |
|------------------|----------|--|--|
| PEGR... 523016AS | 52 x 30 | | |

Available in the finish: AA - AO - AB. The code of the selected colour must be added to the article code. E.g.: PEGR... 523016AS (chosen finish Anod. silver) PEGRAA 523016AS.


silver, gold and bronze ANOD. ALU. punched with screws and screw anchors
bar length 1,66 LM - pack. 20 Pcs

| Article | H x L mm | | |
|------------------|----------|--|--|
| PEGR... 523016FS | 52 x 30 | | |

The strip of adhesive carborundum (PROGRIP) is not applied. The roll of PGR 20 must be ordered separately (see below).

COLOURS

(for a precise assessment of colours and finishes, see the relative enclosed sheet)



PROGRIP is a self-adhesive product in carborundum consisting of a plastic film plus abrasive granules with high resistance to wear. It is normally used to guarantee safety on steps in public and private environments, as required by accident-prevention laws. Available in various colours and widths to meet all technical and aesthetic requirements. It is advisable to apply 2 strips on each step, rounding off the ends.




ADHESIVE CARBORUNDUM NON-SLIP STRIP for STEPS

rolls length 18,2 LM

| Article | Width mm | | |
|-------------------------|----------|--|--|
| PGRN 20 (black colour) | 20 | | |
| PGRB 20 (white colour) | 20 | | |
| PGRN 20 (transparent) | 20 | | |
| PGRG 20 (grey colour) | 20 | | |
| PGRY 20 (yellow colour) | 20 | | |
| PGRM 20 (brown colour) | 20 | | |
| PGRN 25 (black colour) | 25 | | |
| PGRB 25 (white colour) | 25 | | |
| PGRN 25 (transparent) | 25 | | |
| PGRG 25 (grey colour) | 25 | | |
| PGRY 25 (yellow colour) | 25 | | |
| PGRM 25 (brown colour) | 25 | | |
| PGRN 50 (black colour) | 50 | | |
| PGRB 50 (white colour) | 50 | | |
| PGRN 50 (transparent) | 50 | | |
| PGRG 50 (grey colour) | 50 | | |
| PGRY 50 (yellow colour) | 50 | | |
| PGRM 50 (brown colour) | 50 | | |

COLOURS



(for a precise assessment of colours and finishes, see the relative enclosed sheet)


LAYING INSTRUCTIONS

1: Thoroughly clean and degrease the surface of application. 2: Round the ends of the strips. 3: Remove the protective paper from the adhesive and lay the PROGRIP using a roller. 4: Do not apply the strips at temperatures below 15°, otherwise heat the strips and the step. 5: When necessary clean away impurities with a brush and preserve the PROGRIP. 6: When laying on tiles, cut and round the corners of the strips on the inner part of the tile. 7: Carefully seal the outer edges of the strips to prevent water infiltration.

PROEND GRIP


SILVER, GOLD and BRONZE ANOD. ALUMINIUM
+ NON-SLIP INSERT

PEGR... 5230A/F



stair nosing for existing steps

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




1: Choose the suitable profile for covering the edge of the step. 2: Clean the surface on which the profile is to be laid, ensuring that it is grease-free and dry. Do not apply the strips at temperatures below 15°. 3: Remove the protective paper from the adhesive and lay correctly by applying pressure evenly over the whole profile without using a hammer.

If the punched PROEND GRIP has been chosen, screw the profile to the step and apply the adhesive carborundum to hide the screws.

PROGRIP

ADHESIVE CARBORUNDUM - 6 COLOURS



non-slip strip for steps

EXAMPLES OF LAYING

