



SOL 40P Self-adhesive is a joint/threshold cover profile in aluminium covered with film in 27 wood-effect finishes, which is highly resistant to pedestrian traffic, wear, UV rays and commonly used floor cleaning products. Easy to lay and to match with any wood finish; the surface has an open pore embossed finish. Recommended for covering joints between floors in laminate, wood, ceramic tiles, etc.



Available in the wood finishes: 01W - 02W - 03W - 04W - 05W - 06W - 07W - 08W - 09W - 10W - 11W - 12W - 13W - 14W - 15W - 16W - 17W - 18W - 19W - 20W - 21W - 22W - 23W - 24W - 25W - 26W - 27W. The code of the selected colour must be added to the article code. E.g.: PNSP... 40 PA (chosen finish light maple) PNSP01W 40 PA.

ALUMINIUM COVERED (27 wood finishes) with ADHESIVE
Width 40 mm - bar length 2,7 LM - pack. 10 Pcs - 27 LM

Article	L mm		
PNSP... 40 PA	40		

ALUMINIUM COVERED (27 wood finishes) with ADHESIVE
bar length 0,90 LM


Article	L mm		
PNSP... 409 PAS	40		

ALUMINIUM COVERED (27 wood finishes) with ADHESIVE
bar length 1 LM


Article	L mm		
PNSP... 4010 PAS	40		

SOL 40P SELF-ADHESIVE

ALUMINIUM
27 WOOD FINISHES



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1: Choose the adhesive SOL 40 in the required finish. 2: Cut the profile to the required length and clean, degrease and dry the surface, checking that the temperature for application is at least 15°. 3: Remove the protective paper from the adhesive and lay the profile correctly applying a uniform vertical pressure by hand without moving the profile and without using iron/steel hammers.

threshold - joint-cover profiles


PROCOVER WOOD is a joint-cover profile in aluminium covered with a very strong film available in 10 wood finishes. It is applied at the end of laying two adjoining floors with the same height, having left a 6 - 24 mm gap between the two floors set in a thin bed of adhesive. It protects the outside edges of the floor/covering. It is easy to lay and attractive. The design of the profile with lower vertical arrowhead part allows excellent anchorage with the silicone/adhesive.




ALUMINIUM 10 WOOD FINISHES
bar length 2,7 LM - pack. 40 Pcs - 108 LM

Article	L x H mm		
PCRA... 149	14 x 9		
PCRA... 269	26 x 9		

Available in the wood finishes: 01W - 02W - 03W - 04W - 05W - 06W - 07W - 08W - 09W - 10W. The code of the selected colour must be added to the article code. E.g.: PCRA... 149 (chosen finish light maple) PCRA01W 149.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1: Choose the "PROCOVER" with the width suitable for the gap between the two floors to be joined, taking into consideration 2/3 mm side lap. 2: Fill the gap with single-pack Silicone or with the adhesive used for laying the floor. 3: Bury the profile into the adhesive, making sure that both side laps of the profile rest on the coverings to be joined.

threshold - joint-cover profiles

COLOURS

(for a precise assessment of colours and finishes, see the relative enclosed sheet)



PROCOVER INSERT

VINYL RESIN / BLACK RUBBER


Vinyl resin/rubber profile "U-form" for inserting PROCOVER with PINBFT 45 or PINBFT 40 Proinsert System base.

VINYL RESIN / RUBBER
length 2,7 LM and/or in rolls


Article		
PCPCR		

PROINSERT BASE 45 and BASE 40 - ALU. PUNCHED/PERFORED
bar length 2,7 LM - pack. 20 Pcs - 54 LM

Article	Width mm		
PINBFT 45	45		
PINBFT 40	40		



PCRA... 149/1499/209/269
+ INS
+ BASE 45/40




SOL 30 SELF-ADHESIVE


ALUMINIUM
10 WOOD FINISHES

SOL 30 Self-adhesive is a joint/threshold cover profile in aluminium covered with film in 10 wood-effect finishes, which is highly resistant to pedestrian traffic, wear, UV rays and commonly used floor cleaning products. Easy to lay and to match with any wood finish; the surface has an open pore embossed finish. Recommended for covering joints between floors in laminate, wood, ceramic tiles, etc.


threshold - joint-cover profiles



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1: Choose the adhesive SOL 30 in the required finish. 2: Cut the profile to the required length and clean, degrease and dry the surface, checking that the temperature for application is at least 15°. 3: Remove the protective paper from the adhesive and lay the profile correctly applying a uniform vertical pressure by hand without moving the profile and without using iron/steel hammers.



ALUMINIUM COVERED (10 wood finishes) with ADHESIVE
Width 30 mm - bar length 2,7 LM - pack. 10 Pcs - 27 LM

Article	L mm
PINS...30A	30



ALUMINIUM COVERED (10 wood finishes) with ADHESIVE
bar length 0,90 LM

Article	L mm
PINS...309AS	30


Available in the wood finishes: 01W - 02W - 03W - 04W - 05W - 06W - 07W - 08W - 09W - 10W. The code of the selected colour must be added to the article code. E.g.: PINS... 30A (chosen finish light maple) PINS01W 30A.

ZERO CURVE SELF-ADHESIVE


ALUMINIUM
27 WOOD FINISHES

ZERO CURVE Self-adhesive is a transition profile in aluminium covered with film in 27 wood-effect finishes, which is highly resistant to pedestrian traffic, wear, UV rays and commonly used floor cleaning products. Easy to lay and to match with any wood finish; the surface has an open pore embossed finish. Recommended for covering joints between floors in laminate, wood, ceramic tiles, etc.

transition profiles



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1: Choose the ZERO CURVE with adhesive with the required finish. 2: Cut the profile to the required length and clean, degrease and dry the surface, checking that the temperature for application is at least 15°. 3: Remove the protective paper from the adhesive and lay the profile correctly applying a uniform vertical pressure by hand without moving the profile and without using an iron/steel hammer.



ALUMINIUM COVERED (27 wood finishes) with ADHESIVE
Width 40 mm - bar length 2,7 LM - pack. 10 Pcs - 27 LM

Article	L mm
PINZ...07A	40



ALUMINIUM COVERED (27 wood finishes) with ADHESIVE
bar length 0,90 LM

Article	L mm
PINZ...079AS	40

Available in the finish: 01W - 02W - 03W - 04W - 05W - 06W - 07W - 08W - 09W - 10W - 11W - 12W - 13W - 14W - 15W - 16W - 17W - 18W - 19W - 20W - 21W - 22W - 23W - 24W - 25W - 26W - 27W. The code of the selected colour must be added to the article code. E.g.: PINZ... 07A (chosen finish light maple) PINZ01W 07A.

COLOURS

(for a precise assessment of colours and finishes, see the relative enclosed sheet)

