





**PROFIMAL CURVE** are a range of edging and joining profiles that may be curved/shaped. They feature a special system of perforations allowing them to be bent easily so that particular geometric shapes may be easily obtained in situ. This allows decorative patterns to be created at will according to technical and aesthetic requirements and with a separation of 8 mm of sandable profile. The product is made in natural brass in 2.7 m bars and heights of 8, 10 and 12.5 mm.




**NATURAL BRASS thermo packed**  
bar length 2,7 LM - packaging 20 Pcs - 54 LM

Article	H mm		
PRFONCV 08	8		
PRFONCV 10	10		
PRFONCV 125	12,5		

#### COLOURS




(for a precise assessment of colours and finishes, see the relative enclosed sheet)




## PROFIMAL CURVE

NATURAL BRASS  
CURVABLE





#### EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



- 1: Choose the PROFINAL CURVE in the required height and material.
- 2: Cut the profile to the necessary length, calculating the total length.
- 3: Bend the profile mechanically with the PROCURVE MACHINE.
- 4: If necessary fix with screws and screw anchors or simply insert the punched base under the floor laid with the same adhesive. Any oxidation marks may be easily removed with specific chemical products (Sidel-Smac, etc.).

If it is used as a joining profile, bring each floor to the edge of the profile.

**PROFIMAL CURVE** are a range of edging and joining profiles that may be curved/shaped. They feature a special system of perforations allowing them to be bent easily so that particular geometric shapes may be easily obtained in situ. This allows decorative patterns to be created at will according to technical and aesthetic requirements and with a separation of 8 mm of sandable profile. The product is made in silver anodised aluminium in 2.7 m bars and heights of 8, 10 and 12.5 mm.



**SILVER ANODISED ALUMINIUM**  
bar length 2,7 LM - packaging 40 Pcs - 108 LM

Article	H mm		
PRFAACV 08	8		
PRFAACV 10	10		
PRFAACV 125	12,5		

#### COLOURS




(for a precise assessment of colours and finishes, see the relative enclosed sheet)




## PROFIMAL CURVE

SILVER ANODISED ALUMINIUM  
CURVABLE



#### EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



- 1: Choose the PROFINAL CURVE in the required height and material.
- 2: Cut the profile to the necessary length, calculating the total length.
- 3: Bend the profile mechanically with the PROCURVE MACHINE.
- 4: If necessary fix with screws and screw anchors or simply insert the punched base under the floor laid with the same adhesive. Any oxidation marks may be easily removed with specific chemical products (Sidel-Smac, etc.).

If it is used as a joining profile, bring each floor to the edge of the profile.