

SOL 4CP range comprises a large assortment of universal jointing profiles in **aluminium** covered with PVC film that is highly resistant to pedestrian traffic, wear, UV rays and commonly used floor cleaning products. Thanks to the insert in rigid PVC (non-conducting) between the base and the top, the new **SOL 4CP** stops and eliminates electrostatic charges and magnetic fields and whatever else may be transmitted between two floors (e.g.: heated floors). Twenty-seven wood-effect finishes: light maple, dark maple, light beech, dark beech, light dumast, dark dumast, light cherry, dark cherry, walnut, wenge ... plus six anodised finishes (3 available on demand). Any insert of height H: 7, 9, 11, 13, 15 and 19 mm may be used with either the punched/perforated base for screwing or for gluing. Covering width 40 mm.

SOL 4CP

TOP + PIN INSERT + ALUMINIUM BASE
27 wood finishes and 6 anodised finishes



ALU. TOP + PIN INSERT + ALU. BASE 45 PUNCHED/PERFORED
(6 anod. al. finishes of which 3 on demand) - bar length 2,7 LM - pack. 20Pcs - 54 LM


Article	H mm		
PISPC... 407 (PIN insert 07)	7 / 8		
PISPC... 409 (PIN insert 09)	9 / 10		
PISPC... 4011 (PIN insert 11)	11 / 12		
PISPC... 4013 (PIN insert 13)	13 / 14		
PISPC... 4015 (PIN insert 15)	15 / 16		
PISPC... 4019 (PIN insert 19)	19 / 21		

ALU. TOP + PIN INSERT + ALU. BASE 45 PUNCHED/PERFORED
(27 wood finishes) - bar length 2,7 LM - pack. 20Pcs - 54 LM


Article	H mm		
PISPC... 407 (PIN insert 07)	7 / 8		
PISPC... 409 (PIN insert 09)	9 / 10		
PISPC... 4011 (PIN insert 11)	11 / 12		
PISPC... 4013 (PIN insert 13)	13 / 14		
PISPC... 4015 (PIN insert 15)	15 / 16		
PISPC... 4019 (PIN insert 19)	19 / 21		

COMPLETE

Available in the finishes: AO - AA - AB - 01W - 02W - 03W - 04W - 05W - 06W - 07W - 08W - 09W - 10W - 11W - 12W - 13W - 14W - 15W - 16W - 17W - 18W - 19W - 20W - 21W - 22W - 23W - 24W - 25W - 26W - 27W (AT, CH and SB available upon request with a minimum quantity order of 540 LM). The code of the selected colour must be added to the article code. E.g.: PISPC... 407 (chosen finish Anod. gold) PISPCAO 407.

ALU. TOP + PIN INSERT + ALU. BASE 45 PUNCHED/PERFORED
(6 anod. al. finishes of which 3 on demand) - bar length 0,90 LM 

Article	H mm		
PISPC... 407S (PIN insert 07)	7 / 8		
PISPC... 409S (PIN insert 09)	9 / 10		
PISPC... 4011S (PIN insert 11)	11 / 12		
PISPC... 4013S (PIN insert 13)	13 / 14		
PISPC... 4015S (PIN insert 15)	15 / 16		
PISPC... 4019S (PIN insert 19)	19 / 21		

ALU. TOP + PIN INSERT + ALU. BASE 45 PUNCHED/PERFORED
(27 wood finishes) - bar length 0,90 LM 

Article	H mm		
PISPC... 407S (PIN insert 07)	7 / 8		
PISPC... 409S (PIN insert 09)	9 / 10		
PISPC... 4011S (PIN insert 11)	11 / 12		
PISPC... 4013S (PIN insert 13)	13 / 14		
PISPC... 4015S (PIN insert 15)	15 / 16		
PISPC... 4019S (PIN insert 19)	19 / 21		

Available in the finishes: AO - AA - AB - 01W - 02W - 03W - 04W - 05W - 06W - 07W - 08W - 09W - 10W - 11W - 12W - 13W - 14W - 15W - 16W - 17W - 18W - 19W - 20W - 21W - 22W - 23W - 24W - 25W - 26W - 27W (AT, CH and SB available upon request with a minimum quantity order of 540 LM). The code of the selected colour must be added to the article code. E.g.: PISPC... 407S (chosen finish Anod. gold) PISPCAO 407S.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1: Fix and/or glue the base to the floor. 2: Lay the floor leaving from 3 to 10 mm between the floor and the insert. 3: Choose the desired profile, if necessary cut TOP, PIN and BASE at the needed length and then insert the PIN in the TOP in the specific "dovetail" seat. The position the profile above the U-shaped snap-in seat of the base. 4: With the aid of a board, hammer the TOP to the desired fitting level.

COLOURS

(for a precise assessment of colours and finishes, see the relative enclosed sheet)

ANODIZED						AVAILABLE MINIMUM QUANTITY 540 LM					