**PROSLIDER** is a sloping terminal transition profile designed to join different height floors in a perfect, stepless way. This particularly sturdy profile withstands and supports high loads and frequent passage of manual trolleys and vehicles in addition to protecting the edge of the higher floor. **PROSLIDER** is used in particular to join tile or wood to an existing floor. Available in natural and anodized silver aluminium in various heights to accommodate all differences in level.

NATURAL ALUMINIUM AND ANODIZED SILVER ALUMINIUM

PROSLIDER



NATURAL ALUMINIUM thermo packed 5 Pcs bar length 2.7 lm - pack. 40 Pcs - 108 lm


PDAN 08	8		
PDAN 10	10		
PDAN 125	12,5		






## ANODIZED SILVER ALUMINIUM thermo packed bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	Hmm	
PDAA 08	8	
PDAA 10	10	
PDAA 125	12,5	





EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the profile with the required height H, material and finish. 2. Fill the profile cavity with adhesive and apply the adhesive onto the area of application. 3. Lay the "PROSLIDER". 4. Align it "flush" with the floor/covering. 5. Use the adhesive to seal any ample interview. empty interstices.

PROSLIDER LR is a sloping terminal transition profile designed to join different height floors in a perfect, stepless way. This particularly sturdy profile withstands and supports high loads and frequent passage of manual trolleys and vehicles in addition to protecting the edge of the higher floor. **PROSLIDER LR** is used in particular to join tile or wood to an existing floor.

Available in natural and anodized silver aluminium in various heights to accommodate all differences in level.



NATURAL ALUMINIUM thermo packed 5 Pcs bar length 2,7 lm - pack. 20 Pcs - 54 lm

	buillengui 2,7 mil pack. 20103 34 mil				
	Article	H mm			
	PDLRAN 10	10	10,63	28,70	
	PDLRAN 125	12,5	13,23	35,72	
	PDLRAN 15	15	15,18	40,99	
0	PDLRAN 20	20	19,25	51,98	

#### COLOURS

AN - Natural alum. AA - Anodized silver alum.



# **ANODIZED SILVER ALUMINIUM thermo packed**


	bar length <b>2,7 im</b> - pack. <b>20 PCS - 54 im</b>			
	Article	H mm		
	PDLRAA 10	10	13,85	37,40
	PDLRAA 125	12,5	15,60	42,12
	PDLRAA 15	15	17,93	48,41
0	PDLRAA 20	20	21,44	57,92

### INSTRUCTIONS FOR LAYING

 Choose the profile with the required height H, material and finish.
Fill the profile cavity with adhesive and apply the adhesive onto the area of application.
Lay the "PROSLIDER LR".
Align it "flush" with the floor/covering. 5. Use the adhesive to seal any empty interstices.

## PROSLIDER LR

## NATURAL ALUMINIUM AND ANODIZED SILVER ALUMINIUM





EXAMPLES OF LAYING

