
# WWW.CONSTRECO.PT



PROSTYLE GRIP ACC is a non-slip profile in AISI 304/1,4301-V2A satined stainless steel, consisting of a 40 or 60 mm horizontal top with a groove for the insertion of a non-slip carborundum stripe and a 20mm vertical flat side. The profile can be fixed with adhesive film or with screws. The particular design of this profile makes it an elegant and appreciated solution also for modern stairs.





1.60 mm

40 mn



Ρ


Ρ

COLOURS

ACS - Satin finish stainless stee AISI 304/1.4301-V2A







SATIN FINISH STAINLESS STEEL AISI 304/1.4301-V2A with protective film

| Article L mm       |     |
|--------------------|-----|
| SYGRACS 6020A 60 😽 | PSY |
| SYGRACS 6020F 60 🖈 | PSY |

The adhesive carborundum strip (PROGRIP) is not included with the profile. For PSYGRACS 6020A/F order PGR... 40 (Specify the chosen colour).

END CADS STAINIESS STEEL - D/L - pack 2 Des - (1 P and 1 L)


| LIND CAPS STAINLESS STELL - K/L - patk. 2 PCS - (TK and TE, |          |     |  |  |
|---|----------|-----|--|--|
|   | Article  | Lmm |  |  |
| TPSYGRACS 6020/1  |          | 60  |  |  |
| TPSYGRAC  | S 4020/1 | 40  |  |  |

## SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS

\* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

**PROGRIP** is a carborundum adhesive stripe, consisting of an elastic film coated with high wear resistant abrasive grains. It is usually employed in public as well as in domestic environments to make stair steps non-slip. The stripe is available in different colors and widths to meet any technical and aestetic requirement. If PROGRIP is applied directly on the step covering, it is advisable to apply two stripes on each step, rounding their ends.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



## Version with adhesive

1. Choose the profile according to the desired width and cut it to the necessary length; **2.** Clean the surface on which the profile is to be laid, ensuring that it is dry. Remove the protective film and place the profile, applying adequate pressure on it; **3**. Apply the adhesive non-slip carborundum insert of the desired color.

Punched version

 Choose the profile according to the desired width and cut it to the necessary length;
Mark the position of the holes using the existing holes on the profile as reference;
Drill the step using a drill with 5mm diameter and insert the 5x 25mm screws;
Screw the profile to the step; **5**. Apply the adhesive non-slip carborundum insert of the desired color.

# PROGRIP

ADHESIVE CARBORUNDUM - 7 COLOURS





# ADHESIVE CARBORUNDUM NON-SLIP STRIP for STEPS

| rolls length <b>18,2 lm</b> |          |  |   |
|-----------------------------|----------|--|---|
| Article                     | Width mm |  |   |
| PGRN 25 (black colour)      | 25       |  |   |
| PGRB 25 (white colour)      | 25       |  |   |
| PGRT 25 (transparent)       | 25       |  |   |
| PGRG 25 (grey colour)       | 25       |  |   |
| PGRY 25 (yellow colour)     | 25       |  |   |
| PGRM 25 (brown colour)      | 25       |  |   |
| PGRN 40 (black colour)      | 40       |  |   |
| PGRB 40 (white colour)      | 40       |  |   |
| PGRT 40 (transparent)       | 40       |  | * |
| PGRG 40 (grey colour)       | 40       |  | * |
| PGRY 40 (yellow colour)     | 40       |  | * |
| PGRM 40 (brown colour)      | 40       |  |   |
|                             |          |  |   |

## COLOURS

|   | N - Black  | <b>B</b> - W  | B - White   |   | T - Transparent |  |  |
|---|--|---------------|---|---|-----------------|--|--|
|   |  |               |   |   |                 |  |  |
|   | G - Gray   | <b>Y</b> - Ye | llow  | М | - Brown         |  |  |
|   | <b>GN</b> - Yellow/Black                                 |               | The PGRT (trasparent) are not suitable for outside use. |   |                 |  |  |
|   | ADHESIVE NON-SLIP STRIP for STEPS - rolls length 18,3 Im |               |   |   |                 |  |  |
|   | Article  | Widt          | h mm  |   |                 |  |  |
| 0 | PGRGN 20 (yellow/bla                                     | ck)           | 20  |   |                 |  |  |
| 0 | PGRGN 25 (yellow/bla                                     | ck) Z         | 25  |   |                 |  |  |
| 0 | PGRGN 50 (yellow/bla                                     | ck) 5         | 50  |   |                 |  |  |

SATIN FINISH STAINLESS STEEL AISI 304/1.4301-V2A with protective film bar length 2,7 lm - pack. 20 Pcs - 54 lm

bar length 2,7 lm - pack. 20 Pcs - 54 lm Article GRACS 4020A 40

L mm 40

Articles not for sale singly

GRACS 4020F

For PSYGRACS 4020A/F order PGR... 25 (Specify the chosen colour).