


PROTERMSTEP

POLISHED, SATIN FINISH STAINLESS STEEL AISI 304/1.4301-V2A

PROTERMSTEP ACC is the new step cover profile made of stainless steel. Designed to protect the edge of the step and to hide the joint between the tread and the step rise. The special notched shape in the upright stem provides it with excellent anchorage between floor/glue/profile. Reversible profile.









POLISHED STAINLESS STEEL AISI 304/1.4301-V2A with protective film bar length **2,7 lm** - pack. **15 Pcs** - **40,5 lm**

Article	h/Hmm	
PTSPAC 0815	08 / 15	
PTSPAC 10125	10 / 12,5	
PTSPAC 1530	15 / 30	
PTSPAC 2025	20 / 25	

EXTERNAL CORNERS - pack. 10 Pcs

Article	h/Hmm	
REPTSAC 0815	08 / 15	
REPTSAC 10125	10 / 12,5	
REPTSAC 1530	15 / 30	
REPTSAC 2025	20 / 25	

JUNCTION H 10 - 12,5 - 15 - 20 mm - pack. 10 Pcs

Article	h/Hmm		
GIPTSAC 0815	08 / 15		
GIPTSAC 10125	10 / 12,5		
GIPTSAC 1530	15 / 30		
GIPTSAC 2025	20 / 25		



SATIN FINISH STAINLESS ST. AISI 304/1.4301-V2A

bar length 2.7 lm - pack. 15 Pcs - 40.5 lm

Article	h/Hmm		
PTSPACS 0815	08 / 15		*
PTSPACS 10125	10 / 12,5		*
PTSPACS 1530	15 / 30		*
PTSPACS 2025	20 / 25		*

COLOURS

	ON DEMAND
AC - Polished stainless st. AISI 304/1.4301-V2A	ACS - Satin finish stainless st. AISI 304/1.4301-V2A






SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS

PROTERMSTEP

NATURAL AND ANODIZED SILVER **ALUMINIUM**

PROTERMSTEP ALL is the new step cover profile made of natural and anodized aluminium. Designed to protect the edge of the step and to hide the joint between the tread and the step rise. The special notched shape in the upright stem provides it with excellent anchorage between floor/glue/profile.




PTSPAN/AA 125

PTSPAN/AA 15 H 15 mm

10 mr

H 12.5 mm

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS





NATURAL ALUMINIUM

bar length 2,7 lm - pack. 20 Pcs - 54 lm

bar remgan = 1. nm pacia = 0		
Article	H mm	
PTSPAN 08	8	
PTSPAN 10	10	
PTSPAN 125	12,5	
PTSPAN 15	15	

1. Choose the PROTERMSTEP in the required width and colour according to the thickness of the tile (stairs). **2.** First fix the riser part, according to the thickness of the tile (stairs). 2. Hist fix the riser part, placing it at the correct and final height. 3. Fill the empty spaces under the profile with the tile adhesive. 4. Apply the adhesive to the tread, lay the profile with the punched base fully sunk into the adhesive and align the profile so that its lip covers the edge of the riser tile. 5. Lay the tread tiles, aligning them so that they are flush with the upper and rear part of the profile and filling the internal part with adhesive.



ANODIZED SILVER ALUMINIUM thermo packed

bar length 2.7 lm - pack. 20 Pcs - 54 lm

Article	H mm	
PTSPAA 08	8	
PTSPAA 10	10	
PTSPAA 125	12,5	
PTSPAA 15	15	

COLOURS

AN - Natural aluminium	AA - Anodized silver aluminium

