

Aluminium angle edging for hard landscaping

L-profile aluminium edge restraint for hard landscape surfaces available in either Flexible or Rigid lengths in various heights and thicknesses. Flexible lengths shown in the images above. Powder coat finishes available on request.



Benefits:

- Highest quality, durable aluminium alloy won't rust
- Create clean curved or straight lines by hand
- Fast, simple installation saves time and money
- Strong base with tapered top edge gives stability to a refined design
- Works between all hard/soft surface types

Suitable for:

- Suitable for:
- Blocks and pavers
- Asphalt and tarmac
- Wet-pour rubber safety surfacing
- Resin bound gravel



Edging Height		15 mm	18 mm	25 mm	40 mm	50 mm	65 mm	75 mm	100 mm	120 mm	150 mm
Flexible version		101032	101010	101012	101014	101016	101018	101020	101022	101024	101028
Rigid Version		101033	101011	101013	101015	101017	101019	101021	101023	101025	101030
Dimensions	Edging thickness (top bead)	5 mm	5 mm	5.5 mm	6 mm	6 mm	6 mm	6.5 mm	6.5 mm	7 mm	8.5 mm
	Edging length	2500 mm	2500 mm	2500 mm	2500 mm	2500 mm	2500 mm	2500 mm	2500 mm	2500 mm	2500 mm
	Edging foot width	30 mm	30 mm	45 mm	45 mm	45 mm	45 mm	70 mm	70 mm	70 mm	70 mm
	Fixing stake length	N/A	N/A	250 mm	250 mm	250 mm	250 mm	250 mm	250 mm	250 mm	250 mm
Other	Minimum radius by hand*	1000mm							1500 mm		
	Minimum radius in factory	300mm					400 mm	500 mm	600 mm		
	Available finishes	Mill finish/ powder coat to order									
	Material Specification	6063A aluminium									
	Recycled content	Part recycled/ 100% recyclable									