


## FSV 500


DESIGNED FOR HEAVY LOADS

## MIGUMAX

SEISMIC RESISTANT EXPANSION JOINT SOLUTIONS



- 1 Solid all-metal expansion joint cover**  
hard wearing, maintenance-free, long lasting
- 2 Expansion joint top removable**  
at any time
- 3 Multidimensional movement capability**
- 4 Easy and safe mounting by MultiHole sides**

Expansion joint cover	Joint width max. $b_f \text{ max}$ (mm)	Total movement thermal $\Delta b_f$ (mm)	Total movement seismic $\Delta b_f$ (mm)	Visible width $b_s$ (mm)	Width total $b_t$ (mm)	Installation height $h$ (mm)	Load bearing capacity 
FSV 500/45	400	100 ( $\pm 50$ )	200 ( $\pm 100$ )	498	620	45	pedestrians
FSV 500/80	400	100 ( $\pm 50$ )	200 ( $\pm 100$ )	498	620	80	pedestrians
FSV 500/130	400	100 ( $\pm 50$ )	200 ( $\pm 100$ )	498	620	130	pedestrians

Joint width by the time of installation. Potential tolerance:  $\pm 10$  mm

Also available in smaller width (as FSV 280, FSV 285 and FSV 335)

Corner versions will be designed individually. Details submitted project-wise on request.

Further joint widths available on demand.

**Production length:** 3 m

**Standard colour:** Aluminium

