FL 21

FOR FLOORS AND WALLS

MIGUTEC

IOINT COVERS FOR EXPANSION JOINTS.



Flexible high quality elastomeric insert

Hard wearing, temperature resistant (-30°C to +120°C), replaceable

Multi directional movement

Quick and easy installation

Solid, but light aluminium brackets for quick installation in screed or tiled floorings

MultiHole mounting bracket

for secure fixing

| Expansion joint cover | Joint width | Total movement | Visible width | Joint v | width total | Joint height | Load bearing capacity |
|-----------------------|----------------|--------------------|------------------------|------------|-------------|--------------|-----------------------|
| | | | | | | | ₹ |
| | bf max [mm] | Δbf [mm] | b _S [mm] | bt [mm] | | h [mm] | [kN] |
| FL 21/20 | 20 | 5(+3/-2) | 21 | | 80 | 20 | 30 |
| FL 21/35 | 20 | 5(+3/-2) | 21 | | 107 | 35 | 30 |
| FL 21/50 | 20 | 5(+3/-2) | 21 | | 107 | 50 | 30 |

^{*} no continuous use

All information on load bearing capacity does only apply to non-floating floors.

For installation in asphalt, please ask for our technical advice.

Production length: 4 m **Standard colours:** black, grey **Wall connections:** E3, E4

