FS 105

FOR HEAVY DUTY FLOORS

MIGUTRANS

HEAVY-DUTY ALL-METAL JOINT SOLUTIONS



- Symmetrical visible surface has no gaps avoids dirt accumulation
- 2 Solid all-metal expansion joint hard wearing, maintenance-free, long lasting
- **Articulated telescoping system** absorbs movement in 3 directions
- MultiHole mounting bracket for secure fixing

Now available Anodized!

This expansion joint cover is on offer in anodized colours as of now. Available as standard in the four colours shown below, we will be pleased to offer you further colours upon request

Expansion joint cover	Joint width max.	Total movement	Visible width	Joint width total	Joint height		Load bearing capacity	Load bearing capacity	Load bearing capacity
	b f [mm]	Δbf [mm]	b _S [mm]	bt [mm]	h [mm]		kn]	[kN]	solid plastic tyres [kg/mm]
FS 105/22 *	75	20 (±10)	105	221	2:	2	600	130	15
FS 105/30	75	20 (±10)	105	221	31	0	600	130	15
FS 105/42	75	20 (±10)	107	223	4:	2	600	130	15
FS 105/52	75	20 (±10)	107	223	5:	2	600	130	15
FS 105/62	75	20 (±10)	107	223	6:	2	600	130	15

^{*} Minimum joint width 75 mm.

Production length: 4 m

Standard colour: Aluminium, available in anodized version, too

Further installation heights on request.

Corner versions:



