



PROKERLAM SQUARE

ANODIZED SILVER, POLISHED CHROME AND GOLD ALUMINIUM



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



PROKERLAM JOLLY ANODIZED AND POLISHED ALUMINIUM

SILVER, CHROME AND GOLD



EXAMPLE FOR LAYING



PROKERLAM

LINE

ANODIZED AND POLISHED ALUMINIUM SILVER, CHROME AND GOLD



EXAMPLE FOR LAYING





external corners of coverings with low thickness. It can be used like connection profile between step tread and riser of stairs coated with ceramic and mosaic with low thickness. Its particular section and the availability in three different finishes make **PROKERLAM SQUARE** a much sought-after profile that allows a workmanlike application even with low thickness coverings.

PROKERLAM SOUARE is a square corner bead profile in anodized and polished aluminium suitable to protect the

ANODIZED SILVER ALUMINIUM thermo packed bar length 2,7 Im - pack. 40 Pcs - 108 Im

Article H mm PKLQAA 045 4,5

POLISHED CHROME/GOLD ALUMINIUM thermo packed bar length 2,7 Im - pack. 40 Pcs - 108 Im

Article	Hmm		
PKLQBC 045	4,5		
PKLOBO 045	4.5		+

 Choose "PROKERLAM SQUARE" according to the desired finish.
 Cut "PROKERLAM SQUARE" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROKERLAM SQUARE" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
 Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.





PROKERLAM JOLLY is a quarter-circle rounded bead profile in anodized and polished aluminium suitable to protect the external corners of coverings with low thickness. It can be used like connection profile between step tread and riser of stairs coated with ceramic and mosaic with low thickness. Its particular section and the availability in three different finishes make **PROKERLAM JOLLY** a much sought-after profile that allows a workmanlike application even with low thickness.

ANODIZED SILVER ALUMINIUM thermo packed bar length 2,7 Im - pack. 40 Pcs - 108 Im Article H mm PKLJAA 045 4,5 * POLISHED CHROME/GOLD ALUMINIUM thermo packed bar length 2,7 Im - pack. 40 Pcs - 108 Im Article H mm PKLJBC 045 4,5 * PKLJBC 045 4,5 *



COLOURS



PROKERLAM LINE is a Y-shaped profile in anodized and polished aluminium suitable to protect the external corners of coverings in low thickness. It can be used like connection profile between step tread and riser of stairs coated with ceramic and mosaic with low thickness. Its particular section and the availability in three different heights and finishes and special pieces such as internal and external corners, end caps and joints make **PROKER-LAM LINE** a much sought-after profile that allows a workmanlike application even with low thickness coverings.

ANODIZED SILVER ALUMINIUM thermo packed bar length 2,7 Im - pack. 40 Pcs - 108 Im							
Article	Hmm						
PKLLAA 045	4,5						
PKLLAA 10	10						
PKLLAA 125	12,5						
POLISHED CHROME/GOLD ALUMINIUM thermo packed bar length 2,7 Im - pack. 40 Pcs - 108 Im							
Article	Hmm						

PKLLBO 045	4,5	
PKLLBC 045	4,5	
PKLLBC 10	10	
PKLLBC 125	12,5	

COLOURS
AA - Anodized silver alum.
BC - Polished chrome alum.
BO - Polished gold alum.

